



**DEXTER**  
LAUNDRY

## On-Premise Mega-Load T-900 Washer

(Model WCVD60HCS-12)



## On-Premise Mega-Load T-900 Washer

Dexter washers are engineered for the laundry owner demanding greater efficiency, performance, and programming capabilities.

### Durable Design

- **304 Stainless Steel cylinder, outer tub, top, front, and side panels** keep Dexter washers looking good
- **Heavy-duty Sur-Coat Frame** is built like a battleship to last a lifetime
- **Over-sized bearings and seals** run smooth and add to machine life

### VFD Technology

- **Reduce installation cost** by using single or three phase power
- **Extend motor life** by ramping current inrush
- **Save electricity** with lower running amperage draw
- **Lower electricity demand** by eliminating spike usage

### 140 G-Force Extraction

- **Save drying energy** with 140 G-Force washers that remove more water
- **Enhance customer turnover** with better washer and dryer performance
- **Achieve consistent results** throughout all washer sizes

### Powerful Controls

- **Palm OS®** with built-in infrared port
- **Save programming time** using a handheld computer running optional Palm OS® software
- **Easily customize** cycles, water temperatures, supply inputs and more

### Customer Friendly Design

- **Large, easy to use door** for convenient loading and unloading
- **Easily connected** to automatic supply injection systems
- **Easy-to-read digital display** including cycle time remaining information
- **Soft touch cycle selection buttons** with temperature icons
- **Ultra-quiet machine operation** improves the laundry environment



## T-900 OPL Washer Specifications

### CAPACITY

Load Size	Mega Load	
Dry Weight Capacity	60 lbs.	27.2 kg
Cylinder Diameter	30"	76.2 cm
Cylinder Depth	22"	55.9 cm
Cylinder Volume	9 cu ft	255.1 dm <sup>3</sup>

### DIMENSIONS

Cabinet Height	54"	137.16 cm
Cabinet Width	34.39"	87.31 cm
Overall Depth	38.75"	98.43 cm
Floor to Door Bottom	18.5"	46.99 cm
Door Opening	19.25"	48.90 cm

### WASHING/EXTRACTION

High Extract Speed	140 G-Force	573 RPM
Intermediate Extract Speed	60 G-Force	375 RPM
Washing Speed	43 RPM	
Motor Size	3 HP	2.24 Kw

### ELECTRICAL

Electrical Phase	Single or Three	
Electrical Voltage (60 Hz)	208-240 volts	
Electrical Running (Amps)	8.4	
Circuit Protection (Amps)	20 amp	
Electrical Wire Size	12 gauge	
Electrical Service (Single Phase)	2 wire + ground	
Electrical Service (Three Phase)	3 wire + ground	

### WATER

Water Inlet Size	3/4"	19mm
Water Flow Rate (per minute)	9 gal	34.06 L
Water Pressure (min/max)	30-120 psi	207-827 Kpa
Drain Diameter (O.D.)	3"	7.62 cm
Floor to Center of Drain	7.5"	19.05 cm

### INSTALLATION

Net Weight	1082 lbs	491 kg
Clearance Between Machines	1/2" (min)	1.27 cm
Clearance Behind Machine	24" (min)	60.96 cm
Concrete Thickness	8"	20.3 cm

\* For elevations above 6600 feet or for very hot climates, a 30 amp breaker is recommended due to downrating of circuit breakers under these conditions.



**DEXTER**  
LAUNDRY

#### Dexter Laundry, Inc.

2211 W. Grimes, Fairfield, Iowa 52556  
www.dexterlaundry.com  
1-800-524-2954

© 2007, Dexter Laundry, Inc.

Dexter reserves the right to change features or specifications without notice.



Convenient Soap Dispenser



Easy Programming



Large Loading Door



Heavy Duty Construction