

Cameras

- Super Mini CCD Camera***
- 1/3" Sony Super HAD sensor
- More than 380 TV lines resolution
- 3.6mm lens
- .5 lux minimum illumination
- 12 VDC
- Interior only
- Super small compact size



KPC-S700CB

- Super Mini Pinhole***
- 1/4" Sony Super HAD sensor
- 550 TV lines resolution
- 3.6mm lens
- .5 lux minimum illumination
- 12 VDC
- Interior only
- Super small compact size



KPC-V5N500H

- Faceplate Camera ***
- Ideal for Changer or Playstation
- 1/3" Sony Super HAD
- 380 TV lines resolution
- 1.78mm lens
- .5 lux minimum illumination
- 12 VDC
- IP67 Weather Resistant



KPC S190CDV

- Motion Detector Hidden Camera***
- 1/3" Sony Super HAD
- 480 TV lines resolution
- 3.7mm lens
- .92 lux minimum illumination
- 12 VDC
- Interior only
- Motion detector housing



HI1006

- Smoke Detector Camera***
- 1/3" Sony Super HAD
- 480 TV lines resolution
- 3.7mm lens
- .92 lux minimum illumination
- 12 VDC
- Interior only
- Smoke detector housing for hidden location



HI1011

- Electrical Box Camera ***
- 1/3" Sony Super HAD
- 480 TV lines resolution
- 3.7mm lens
- .92 lux minimum illumination
- 12 VDC
- Non descript Electrical Box
- Small compact size



HI1814

- Weather Proof IR Cam***
- 1/3" Sony Super HAD sensor
- 540 TV lines resolution
- Vari Focal 4-9mm Lens
- 0 lux minimum illumination(LED On)
- Sealed Weather Proof Housing
- Fully Adjustable Mount
- 12VDC



CMR603W

- Weather Proof IR Cam***
- 1/3" Sony Super HAD sensor
- 540 TV lines resolution
- Vari Focal 4-9mm Lens
- 0 lux minimum illumination(LED On)
- Sealed Weather Proof Housing
- Fully Adjustable Mount
- 12VDC



CMR3839

- Weather Proof IR Cam***
- 1/3" Sony Super HAD sensor
- 540 TV lines resolution
- Vari Focal 9-22mm Lens
- 0 lux minimum illumination(LED On)
- Sealed Weather Proof Housing
- Fully Adjustable Mount
- 12VDC



CMR3822

- VariFocal IR Camera**
- 1/3" Sony HQ1 sensor
- 540 TV lines resolution
- 3-9mm adjustable lens
- 0 lux minimum illumination
- 12 VDC
- IP65 Weather Proof Housing



CMR88830H

- Fixed Lens Infrared Bullet ***
- 1/3" Sony Super HAD
- 380 TV lines resolution
- 3.6mm lens
- .3 lux day 0 lux night IR on
- 12 VDC
- Weather resistant housing
- Bracket included



IRPR3314

- Color Weather Proof ***
- 1/4" Panasonic sensor
- 420 TV lines resolution
- 3.6, 6.0, or 8.0mm lens
- 1.0 lux minimum illumination
- 12 VDC
- Sealed weather proof housing
- Fully adjustable mount



CC-9620B

- TagCapture****
- 1/2" Sony B/W Ex-View sensor
- 600 TV lines resolution
- Metaphase type LEDs
- 0 LUX (works in total darkness)
- 12VDC Power Supply included
- Low Power Consumption
- IP66 Weather Proof Housing



DC IRCAM LED

- High Resolution CCD Camera ****
- 1/3" Sony super HAD
- 540 TV lines resolution
- Optional lens available
- .02 lux minimum illumination
- BLC/DNR Chip
- 12 VDC/24 VAC



BX584DNC

- 192X Zoom Day-Night Camera**
- 1/4" Sony Super HAD
- 16x optical zoom
- 12x digital zoom(192x Zoom)
- Day/Night Camera
- 12 VDC
- Excellent Tag Cam
- On Screen Display



AN1221

- High Res/WDR / Day-Night Camera ****
- 1/3" Sony Double Scan sensor
- 480 TV lines resolution
- Optional lens available
- .1 lux minimum illumination
- 12 VDC/24 VAC
- Outdoor Housing available
- On Screen Display



GIN605

- Clear-View High Definition****
- 1/3" Sony Progressive Scan sensor
- 1.3 Megapixel
- VariFocal lens
- .5 lux minimum illumination
- 12 VDC
- Dual codec support MPEG4



DC-IPCAM-13

- Plug & Play IP Camera**
- True Plug & Play
- Wired or Wireless Connection
- 3.2mm lens
- 1.0 lux minimum illumination
- 5 VDC
- Interior only
- Built in Web Server
- Comes with its own software



CAIP1000

*Denotes cameras which are available with our standard package
**Lens sold separately. 3-8mm, 5-50mm, or 5-85mm available.
Others available on special order

Optional Lenses for CCD High Resolution



2-12mm

3-8mm

6-60mm

5-100mm

- Vandal Proof IR Dome***
- 1/3" Sony Super HAD sensor
- 550TV lines resolution
- 4-8mm adjustable lens
- 0 lux minimum illumination
- 12 VDC
- Weatherproof housing
- Illumination up to 90 Feet



CMD708H

- Vandal Proof IR Dome***
- 1/3" Sony Super HAD sensor
- 550TV lines resolution
- 4-8mm adjustable lens
- 0 lux minimum illumination
- 12 VDC
- Weatherproof housing
- Illumination up to 90 Feet



CMD708W

- High Resolution Dome ***
- 1/3" Sony Super HAD sensor
- 560 TV lines resolution
- 4.0-9.0 mm adjustable lens
- .4 lux minimum illumination
- 12 VDC/24VAC
- Interior only



DO564V

- High Resolution Dome**
- 1/3" Sony Super HAD sensor
- 560 TV lines resolution
- 4.0-9.0 mm adjustable lens
- .5 lux minimum illumination
- 12 VDC
- Interior only



PDL 55DNAV

- Vandal Proof/Weather Proof Dome**
- 1/3" Sony Super HAD sensor
- 480 TV lines resolution
- 4.0-9.0 mm adjustable lens
- .4 lux minimum illumination
- 12 VDC
- Indoor or outdoor weatherproof
- 180 degree adjustable housing



VPD 48DNAV

- Day/Night Pan/Tilt/Zoom Dome**
- 1/4" Interline Transfer sensor
- 550 TV lines resolution
- 10x Optical Zoom lens(up to 100x digital)
- .7 lux minimum illumination
- 12 VDC
- Interior only
- Can be controlled remotely



MV-N10T



PT9000

- Day/Night Pan/Tilt/Zoom Dome**
- 1/4" Sony Super HAD sensor
- 480 TV lines resolution
- 36x Optical Zoom lens (up to 432x digital)
- .5 lux minimum illumination
- 24 VAC
- Weather proof housing IP 66 Rated
- Can be controlled remotely